



1460 Santa Anita Avenue - South El Monte, Ca 91733
Phone: (626) 575-2850 - Fax: (626) 575-2405

ACCU-BLEND 1128 HYDROCARBON C-5 RESIN

ACCU-BLEND 1102 RESIN is a C-5 hydrocarbon resin with good heat stability. It is designed to tackify a variety of adhesives such as polymers, hot melts, natural rubber, casting wax & polyisobutylene.

PHYSICAL PROPERTIES	ASTM METHOD	TYPICAL SPECIFICATIONS
SofteningPoint (F)	D-127	100 ©
Color	Gardner	4
Color Stability	Gardner	12
Molten Color	Gardner	6
Melt Viscosity @ 200 ©	D-3236	250
Heat resistance @ 200 ©	ASTM-1544	8.5

WARRANTY DISCLAIMER STATEMENT

The information contained in this document is based on tests which are believed to be reliable. As actual conditions of use may vary and a beyond the control of Accu-Blend Corporation. The Products specified characteristics cannot be guaranteed and are offered solely for the buyers evaluation and verification. There are no warranties, representations or conditions, expressed or implied, of any kind including but n limited to merchantability or fitnessfor a particular purpose made by Accu-Blend Corporation or its officers employees or affiliates, in connec with Accu-Blend Corporation or its officers employees or affiliates, in connection with the sale of the products.

re

not
action